

B08400-00



Description

Automatic Key Deposit Box SD-04

- Key Deposit Box to keep safe the key of the protected building
- in case of a main alarm the outer door will be opened automatically by the Fire Control Panel; only Fire Brigade can open inner door with key for the building
- Stainless steel housing, w/o inner door (see below)
- flush mounting, incl. front frame
- delivered incl. internal heater

Technical specifications :

Operating voltage : 24 V DC
 Alarm current : 200 mA
 Outer door : 5 mm stainless steel
 Walls : 8 mm Alu
 Heater : 5 W, included
 Colour : Stainless steel
 Dimension of housing: 220x220x160 mm (WxHxD)
 Dimension of frame : 275x275x2 mm (WxHxD)

VdS-Nr. G 198 044

B08405-00

Inner door for SD-04, version for profile cylinder locking

- delivered w/o locker
- Dimensions : 205 x 120 x 20 mm (H x W x D)

B08410-00

Inner door for SD-04, version for "Kruse" locking

- delivered w/o locker
- Dimensions : 205 x 120 x 20 mm (H x W x D)

B08426-00



Stand-alone mounting Column for SD-04

- To mount the key deposit box SD-04 in a freely standing column
- The complete column is screwed either by means of platform on an existing foundation or cast in with flat irons into a foundation
- Stainless steel housing

Technical specifications :

Material : Stainless steel, 2 mm
 Weight : 35 kg
 Dimensions : 1200 x 380 x 280 mm
 (H x W x D)

Pay attention : additional freight charge