

B01060-00



Photo : F1-18 in housing
B2 and incl. zone LEDs

Description

**Fire Control Panel "Solution F1-18"
Standard configuration for 2-18 loops
and max. 2.286 detectors / modules with
power supply 7,0 A / 24 V included**

Modular, intelligent and ultra modern Fire Control Panel for analogue addressable detectors and conventional detectors. Prepared for 2 to 18 loops and / or 8 to 72 conventional zones. Supports Hochiki ESP and CDX detectors as well as Apollo Orbis, XP95 and Discovery.

**Additional features compared to
„Solution F1-6“:**

- Panel can control up to 2 286 detectors/ modules
- Power supply 24 V / 7,0 A included
- Slots for max. 9 loop cards and/or conventional detector cards
- A max. of 1.024 zones can be organized
- USB host interface e.g. for USB stick for export of panel data
- Metal rack for additional mounting area inside the panel (for system components)
- Interface for TFT display
- Interface for Touch Screen LCD module
- Slot for SD card to extend data memory
- Interface for audio codec module

Please select housing separately.

Technical specifications :

| | |
|---------------------|----------------------------|
| Mains AC : | 230 V AC, 50/60 Hz |
| Operating voltage : | 24 V DC |
| Quiescent current : | 100 mA |
| Loops / Spurs : | 2 – 18 / 8 - 72 |
| Power supply : | 7,0 A / 24 V |
| Batteries : | max. 70 Ah / 24 |
| Weight : | 17,5 kg with housing A1 |
| Dimensions : | see housings |

VdS approval : G 205 024

VdS System approval : S 205 024